"Your Single Source for All Your Loading Dock Needs"

## Roll-Up Doors: Header & Wall Mount Survey

1) INFORMATION  A. Company:  B. Job Name:  D. Door Name:  2) DIMENSIONS  Please note any possible obstructions or issues that may hinder installating All measurements should be in inches.	on.
B. Job Name:  D. Door Name:  2) DIMENSIONS  Please note any possible obstructions or issues that may hinder installating All measurements should be in inches.	on.
2) DIMENSIONS  Please note any possible obstructions or issues that may hinder installating All measurements should be in inches.	on.
Please note any possible obstructions or issues that may hinder installating All measurements should be in inches.	on.
All measurements should be in inches.	on.
HEAD ROOM	
WIDTH	
SIDE CLEARANCE CLI	SIDE
WIDTH	
3) DOOR MATERIAL 6) OPERATION STYLE	
☐ Bug Barrier® ☐ Manual Spring-Lo	
<ul><li>☐ 22 oz. Vinyl</li><li>☐ 40 oz. Vinyl</li><li>☐ Manual Chain Ho</li><li>☐ Automatic In-Tub</li></ul>	
Internal 120V 52 RPM	Motor
4) DOOR COLOR: Requires 18" of head ro	nal Jackshaft Operator oom and 18" of side room.
other colors are available upon request	☐120V / ☐ 240V ☐ 208V / ☐ 480V / ☐ 600V
5) MOUNT STYLE	
Doors use 8" of head room and 5" to 13" total of side room depending on track width.  7) OPERATION DRIVE SIDE	E: □Right / □ Left
Header Mount / In Jamb As viewed from mounting surface	_
All doors manufactured with +/- 1/8" tolerance.  Wall Mount / Face of Wall  8) WIND STABILIZER	
☐ Interior / ☐ Exterior ☐ Standard Windbar	