Roll-Up Doors: Header & Wall Mount Survey

1)	INFORMATION	
	A. Company:	C. Quote #
	B. Job Name:	D. Door Name:
	2. 000 Hame.]
2)	DIMENSIONS	
		ctions or issues that may hinder installation. nents should be in inches.
	HEAD ROO	ОМ
		WIDTH
	HEIGHT	
	SIDE CLEARANCE	SIDE CLEARANCE
		- WIDTH —
		WIDTH
3)	DOOR MATERIAL	6) OPERATION STYLE
	☐ Bug Barrier®	Manual Spring-Loaded
	22 oz. Vinyl	Manual Chain Hoist
	☐ 40 oz. Vinyl	Automatic In-Tube Motor Internal 120V 52 RPM Motor
4)	DOOR COLOR:	High Cycle External Jackshaft Operator Requires 18" of head room and 18" of side room.
,	Standard stock colors are Green, Blue, Black, and Yellow. A variety of	·
	other colors are available upon request.	Three Phase: □ 208V / □ 480V / □ 600V
5)	MOUNT STYLE	☐ Water-tight (Nema-4)
	Doors use 8" of head room and 5" to 13" total of side room depending on track width.	7) OPERATION DRIVE SIDE: ☐Right / ☐ Left
	Header Mount / In Jamb All doors manufactured with +/- 1/8" tolerance.	As viewed from mounting surface.
	Wall Mount / Face of Wall	8) WIND STABILIZER
	☐ Interior / ☐ Exterior	Standard Windbar. Pocket Color:
		☐ Aluminum Hinges for higher windloads.