

Industrial • Commercial Application Light to Medium Motorized Traffic



8500 shown with optional teardrop bumpers.

DOUBLE ACTING "INSULATED" TRAFFIC DOOR

- INSULATED DOORS
- PIVOTS OFF OF FULL LENGTH DOOR SHAFT
- IDEAL FOR HEAVY PALLET JACK TRAFFIC WHERE TEMPERATURE CONTROL IS REQUIRED

Perma Tech Inc., doors are available in single or double panel.



FEATURES:

- Doors are constructed with rigid PVC framing, aluminum spine and are insulated with expanded polystyrene. Overall thickness is 1 3/4".
- Hinges are V-CAM style with hardened roller bearings, CAM covers and 10" bottom jamb guards.
- Standard windows are 9" x 14" x 1/8" polycarbonate set in low profile high strength sealed plastic frames.
- The doors are clad with .125 ABS high impact plastic facing.
- Available colors are black, canyon blue, green, brown, white, beige, dark gray, light gray and red.
- Doors can be manufactured to fit up to an 10' x 10' bi-parting or 5' x 10' single panel opening. Consult factory for larger openings.

Perma Tech Inc.

363 Hamburg Street • Buffalo, NY 14204
Phone: 716.854.0707 • Fax: 716.854.0774
Sales@PermaTechlnc.com • www.PermaTechlnc.com

RCHITECTURAL


Where indicated on plans, furnish PT-8500 traffic door as manufactured by Perma Tech Inc. Doors are constructed with rigid PVC framing, aluminum spine, and expanded polystyrene insulation. Overall thickness is 1 3/4". Windows are 9" x 14" x 1/8" polycarbonate set in low profile plastic frames. Facing is ABS high impact plastic. Doors are fully gasket. The V-CAMS and the 10" bottom Guards Jam zinc plated. are

To fit door opening size:

____width x ____height

	SINGLE	GLE □ BI-PARTING			
			LEFT	☐ RIGHT	
OP	PTIONS:				
	ardrop bumpe ailable as upgı)).
TE	ARDROP BUM	PERS (BOTH SI	DES)	
	FB12 (12")	☐ FB	18 (18")	☐ FB24 (24	4 ")
	FB30 (30")	☐ FB	36 (36")	☐ FB42 (42	2"
	FB48 (48")				
AB	S IMPACT PLA	ATES (B	OTH SID	ES)	
	PL12 (12")	☐ PL	.18 (18")	☐ PL24 (24	")
	PL30 (30")	☐ PL	.36 (36")	☐ PL42 (42	")
	PL48 (48")				
ST	AINLESS STEE	L IMPA	CT PLAT	ES (BOTH SID	ES)
	SS12 (12")	□ SS	18 (18")	☐ SS24 (24"
	SS30 (30")	□ SS	36 (36")	☐ SS42 (42 "
	SS48 (48")				
JA	MB GUARD OI	PTIONS	;		
	JG10 (10") (S	TND)			

☐ JG18 (18") SS



☐ 9" X 14" (STANDAR	RD)					
	G 22 X22					
DOOR FRAMES						
☐ TUBE STYLE - PRIMED STEEL						
☐ TUBE STYLE - STAINLESS STEEL						
☐ C-CHANNEL - PRIMED STEEL						
☐ C-CHANNEL - STAINLESS STEEL						
OTHER						
• • • • • • • • • • • • • • • • • • • •						
☐ CANE BOLTS	☐ LOCKING SLEEVE					
□ LIMITING POSTS						
☐ SPRING COMPENS.	SPRING COMPENSATOR					
☐ RUB RAILS / CART	RUB RAILS / CART GUARDS					
■ WASHDOWN PACK	AGE					



☐ JG10 (10") SS

PT-8500 Traffic Doors are shipped FOB Factory.

WINDOWS

Customer:		
Approved By:	Date:	

Perma Tech Inc. • 363 Hamburg Street • Buffalo, NY 14204 Sales@PermaTechInc.com • www.PermaTechInc.com