

Industrial • Commercial Application Heavy Motorized Traffic



Picture shown is Model 9500 with optional 24" teardrop bumpers and 14" x 16" vision panel.

DOUBLE ACTING "INSULATED" TRAFFIC DOOR

- INTERNAL STRUCTURAL ALUMINUM FRAMEWORK
- IDEAL FOR FORK LIFT TRAFFIC WHERE TEMPERATURE CONTROL IS REQUIRED
- DOORS ARE USDA ACCEPTED

Perma Tech Inc., doors are available in single or double panel.

FEATURES:

- Doors are constructed with welded aluminum framing, insulated with expanded polystyrene. Overall thickness is 1 3/4".
- Hinges are V-CAM style with hardened roller bearings, CAM covers and 10" bottom jamb guards.
- Standard windows are 9" x 14" x 1/4" acrylic set in low profile high strength sealed plastic frames.
- The doors are clad with ABS high impact plastic facing.
- Available colors are black, canyon blue, green, brown, white, beige, dark gray, light gray and red.
- Doors can be manufactured to fit up to an 10' x 10' bi-parting or 5' x 10' single panel opening. Consult factory for larger openings.

Perma Tech Inc.

363 Hamburg Street • Buffalo, NY 14204
Phone: 716.854.0707 • Fax: 716.854.0774
Sales@PermaTechlnc.com • www.PermaTechlnc.com

RCHITECTURAL ECIFICA

Where indicated on plans, furnish Model 9500 traffic door. constructed with **Doors** are welded aluminum framing polystyrene insulation. Overal Windows are 9" x 14" x 1/4 profile plastic frames. Facing plastic. Doors are fully gaskete the 10" Bottom Jamb plated.

3 are constructed with	W.I.C.	
framing and expanded		
on. Overall thickness is 1 3/4".		
14" x 1/4" Lexan set in low		
s. Facing is ABS high impact		V-CAM ASSEMBLY
lly gasketed. The V-CAMS and		
Jamb Guards are zinc		
		STRUCTURAL ALUMINUM
size:	00	W/FOAM CORE
height		
☐ BI-PARTING	OPTIONAL	
☐ LEFT ☐ RIGHT	TEARDROP BUMPER	JAMB GUARD

OPTIONS:

□ SINGLE

To fit door opening size:

width x _____

Abuse plates, jamb guards, scuff plates, rub rails

and cart guards are available as upgrades.

TEARDROP BUMPERS (BOTH SIDES)

- □ FB12 (12") □ FB18 (18") □ FB24 (24")
- ☐ FB30 (30") □ FB 36 (36") □ FB42 (42"
- ☐ FB48 (48")

ABS IMPACT PLATES (BOTH SIDES)

- □ PL12 (12") □ PL18 (18") □ PL24 (24")
- □ PL30 (30") □ PL36 (36") □ PL42 (42")
- □ PL48 (48")

STAINLESS STEEL IMPACT PLATES (BOTH SIDES)

- ☐ SS12 (12") ☐ SS18 (18") ☐ SS24 (24")
- ☐ SS30 (30") ☐ SS42 (42") ☐ SS36 (36")
- ☐ SS48 (48")

JAMB GUARD OPTIONS

☐ JG10 (10") (STANDARD) □ JG18 (18")

WINDOWS

- **□** 9" X 14" (STANDARD) □ 14" X 16"
- □ 10" X 30" □ 22" X 22"

FACING

- □ ABS (STANDARD)
- ☐ STAINLESS STEEL ☐ GALVANIZED

DOOR FRAMES

- ☐ TUBE STYLE PRIMED STEEL
- **□** TUBE STYLE STAINLESS STEEL
- □ C-CHANNEL PRIMED STEEL
- □ C-CHANNEL STAINLESS STEEL

OTHER

- ☐ CANE BOLTS □ LOCKING SLEEVE
- □ LIMITING POSTS
- □ SPRING COMPENSATOR
- ☐ RUB RAILS / CART GUARDS
- ☐ WASHDOWN PACKAGE



PT- 9500 Traffic Doors are shipped FOB Factory.

Customer:		
Approved By:	Date:	

Perma Tech Inc. • 363 Hamburg Street • Buffalo, NY 14204 Sales@PermaTechInc.com • www.PermaTechInc.com