

PERMA CORE™

TRAFFIC DOOR

SPECIFICATIONS

ROYAL RED



DOOR BODY

Shall be 3/4" thick with high impact full color impregnated ABS facings permanently bonded to a solid core.

The leading edge of each leaf shall have a safety cushioned loop type nosing.

(Optional) high impact bumpers shall be a moulded teardrop design fabricated from a linear low density polyethylene.

MARINE BLUE



DESERT BEIGE



ONYX BLACK



DOVE GRAY



FIELDSTONE GRAY



LEATHER BROWN



DUTCH CHOCOLATE



HARDWARE

Shall be a corrosion resistant cast Meehanite (45/50,000 psi compression) "V" cam design aligned and prepinned to a 1" diameter, cold drawn welded mechanical grade 1020 full height steel tube with a tensile strength of 100,000 psi.

The cam follower shall be fitted with a heat treated steel roller bearing, with LUBRI-DISC® seals. The bearing shall be zone hardened to a load rating of 10,000 newtons.

The hardware assembly and door body shall be secured by means of a full-height extruded solid aluminum anodized mount.

VISION PANELS

Vision panels shall be double glazed, U.L. listed burglary resistant with an optical clarity of 96%. Vision panels shall be mounted as to provide a flush surface with both sides of the door body.



PERMA TECH INC.

363 HAMBURG STREET
BUFFALO, NEW YORK 14204

Toll Free 1-800-362-7325

(716) 854-0707

FAX (716) 854-0774

Your local authorized Perma Tech representative is: